

Thank you for purchasing an Outdoor Revolution product. This product will give years of satisfactory service if basic instructions are followed. Our products are designed for durability, longevity and ease of erection.



WWW.OUTDOOR-REVOLUTION.COM

UNIT 1 BRICK PARK
BRETFIELD COURT
BRETTON STREET INDUSTRIAL ESTATE
DEWSBURY
WEST YORKSHIRE
WF12 9BY

In the interest of continuous development and improvements by Outdoor Revolution; some products or specifications may vary slightly from the photographs and information provided in this instruction manual. Dimensions and weights are approximate and intended as guidelines only.



PORCHLITE 260 AIR L

INSTRUCTIONS & CARE MANUAL



IMPORTANT: PLEASE CHECK YOUR EQUIPMENT

1 X FLYSHEET (OR OUTER)

1 X SINGLE POINT INFLATION OXYGEN AIR FRAME

1 X STEEL ROOF TENSIONING POLE

1 X BAG OF GROUND PEGS

1 X DUAL ACTION HAND PUMP

1 X DRAUGHT SKIRT

1 X REPAIR KIT

1 X CARRY BAG

GUYLINES



We recommend that you insure your motorhome awning against storm damage, or accidental damage, as the warranty does not cover such eventualities. The manufacturer **IS NOT** liable for any damage caused to the motorhome awning, or its contents, due to misuse, incorrect pitching or severe weather conditions; full warranty details can be found on the rear of this booklet.

THE GUARANTEE (CONTINUED)...

registered in accordance with the manufacturer's registration process.

OR reserves the right to appoint its own representative to inspect the awning/tent, tube or associated components, prior to any repair or replacement of part(s) covered.

Replacement INTELLIGENT FRAMES under the lifetime guarantee will be despatched to any UK mainland address free of Charge. Shipping charges covering the cost to dispatch the INTELLIGENT FRAMES to destinations outside of the UK mainland will be applied and payable before being despatched. (**Please note this service may take over 3 days).

Covered components of the Lifetime Warranty

The Lifetime Warranty is valid only for the following components of the awning or tent::

The air tube containing the IF (Intelligent Frame) only

Maintenance repairs and general wear and tear are not covered by the Lifetime Guarantee.

1.3. Customer duties to retain warranty

Online Registration of product is required to validate the Lifetime Warranty; the warranty automatically ceases on re-sale of the product.

The recommended pressure is of 4PSI; as soon as air is heard releasing from the IF valve, inflation must cease.

The warranty does not cover deliberate defacement, human error, misuse or accidental damage; the Lifetime Warranty is a guarantee against manufacturing flaws, solely of the tube.

1.4. Data protection

The activation and validation of the Lifetime Warranty requires OR to maintain personal data of the owner. Blue Diamond Products Limited and Outdoor Revolution will not pass your data onto any third parties and we will not use your data for any marketing purposes without your consent.

LIFETIME GUARANTEE

This warranty provided by the manufacturer does not adversely affect the statutory rights of the purchaser against the seller and gives remedies in addition to those against the seller under the contract of sale. Claims by the purchaser, in particular for a defect on an Intelligent Frame (IF), against the selling Outdoor Revolution distributor remain unaffected by the warranty.

Outdoor Revolution (hereinafter called "OR"), a subsidiary of Blue Diamond Products Ltd group, and its successors in title, warrants for awnings, or tents using IF technology, of their manufacture:

12 months, without limitation, a warranty against all manufacturing defects of the entire product.

1. LIFETIME WARRANTY OF THE INTELLIGENT FRAME FOR THE FIRST REGISTERED OWNER

1.1. Duration of Warranty

OR undertakes that each new awning/tent supplied thereon by OR as original equipment will be free from defect in material or workmanship according to the state of the art under normal use and service for the Lifetime of the awning/tent. The warranty is valid for the first registered owner of the awning/tent, who bought the product at an OR Authorised Retailer.

The warranty starts on the date of first registration, THIS MUST BE WITHIN 14 DAYS OF PURCHASE.

1.2. Coverage of the Lifetime Warranty

The warranty applies to free of charge repair, or replacement of the IF tube by OR i.e. OR's obligations under this warranty being limited to repairing or replacing at its option any parts or Tube by either OR, or an OR Authorised Repairer. The repair or replacement of defective parts under this undertaking will be made by the Authorised Repairer to whom the awning is returned, free of charge to the customer.

For the parts fitted during a repair, until expiry of the warranty limitation according to Paragraph 1, the same warranty is given as for the awning, tent, frame or associated parts i.e. the warranty is not extended by the repair or replacement of parts even for the parts rectified or replaced. Replaced parts become the property of OR.

Lifetime Warranty cover is dependent upon confirmation that the awning/tent has been

IMPORTANT INFORMATION

- ◆ Please do not leave for your holiday without fully erecting and checking that you have all the listed contents for your motorhome awning. If you are missing anything, then please contact your retailer immediately before use.
- ◆ Please note that man-made fabrics are prone to condensation, when the warm air and moisture within the motorhome awning, comes into contact with the colder air on the outer material. This is a perfectly natural occurrence and should not be confused with leaking. Please ensure that all ventilation points remain open, wherever possible, in order to help combat condensation.
- ◆ We suggest pitching your motorhome awning for some period before use, enabling it to undergo the 'weathering' process. Weathering sometimes requires a few uses of the motorhome awning, before it becomes fully effective. Seam sealant can be used to resolve any persistent weeps; this is a natural process. 'Weathering' is the process of allowing your motorhome awning to become soaked, then dried, approximately two to three times to reinforce the waterproofing of the material seams/stitching.
- ◆ Please ensure that you site the motorhome awning on clear/level ground before erecting, with no sharp objects beneath and zips fully closed. We suggest placing a groundsheet underneath the motorhome awning to keep it dry/clean.
- ◆ We suggest conducting a trial run of your motorhome awning to familiarise yourself with the assembly/usability of it. Should you have any issues in relation to pitching your motorhome awning; please contact a dealer for assistance before your holiday.
- ◆ Please note that this model is designed for touring use and not seasonal pitch.
- ◆ Always dry/air the motorhome awning after use, before packing away, to prevent mildew or mould from developing.
- ◆ Any dirt or stains can be removed by brushing, or gently washing, using warm water. DO NOT use detergents, as this will destroy the waterproofing of the materials.
- ◆ DO NOT cook or smoke inside this motorhome awning; despite the outer fabric being flame-retardant, it will still melt.
- ◆ In the event of damage; please contact your retailer. If, for whatever reason, you are unable to contact them, then please email cs@blue-diamond-products.co.uk and our dedicated customer service team will be happy to assist you.
- ◆ Please avoid using this motorhome awning in temperatures below freezing, as this can result in cracking of the Oxygen Air Frame.
- ◆ Always store your motorhome awning bag flat, never on the side, in a cool/dry area, in order to avoid any detrimental impact on the Oxygen Air Frame.

OPTIONAL ACCESSORIES

- Treadlite 260 —A porous motorhome awning carpet, which is fully breathable and has been cut to size, especially for this model.
- Canopy Poles - A useful pair of steel poles that can be used to hold the front door in an upright position, should you wish to.
- Rear Pad Poles— A useful pair of adjustable upright steel poles to allow a tighter fit of your motorhome awning to your vehicle.
- Lumi-Link Tube Light Kit—A triple remote controlled dimmable roof strip light kit, which enable you to maintain a cosy evening ambience.
- Roof Tension Pole Kit — Steel roof rigidity poles, which are designed to slot into the internal roof pockets for further tension during adverse weather conditions.

⇒ **Selection of chairs and furniture.**

⇒ Visit www.outdoor-revolution.com for more information.

12 MONTH WARRANTY

On the Workmanship & Canvas Against Any Manufacturing Faults.

- Damage caused by incorrect maintenance of the product.
- Flaws in the fabric caused by excessive use.
- Imperfections and pulls in mesh doors due to wear and tear.
- Water ingress through fabric as a result of accelerated UV degradation due to long term pitch .
- Water ingress through seams caused by excessive abrasion of seams or taped seam.
- Broken zips caused by over tensioning, forcing or snagging.
- Over tensioned/stretched seams coming apart.
- Buckles subjected to undue force or abrasion.
- Lost/popped out eyelets.
- Broken holdalls.
- Pole breakages or tube punctures (where applicable).
- Collateral damage from a pole breakage.
- Condensation, (a natural occurrence, exacerbated by insufficient ventilation opening).
- Consequential damage/loss to property/belongings (either inside or outside of the product) or shortening of holidays.

Outdoor Revolution work very closely with our retail partners to manage all warranty repairs/issues:

Please contact your retailer immediately (even if purchased online) if you feel your Outdoor Revolution product has a genuine warranty issue. The retailer, in turn will raise the issue with ourselves and we will action; with the retailer, according to the nature of the claim.

Returning Products

Please ensure the product is clean and dry and as close to its original condition as possible before sending back for checking. Wet or dirty products will not be accepted back for checking/warranty claims.

It is important to note that the Sales Contract between yourself and the retailer you purchased the Outdoor Revolution product from, remains valid throughout any warranty claim and your statutory rights are not affected.

OUTDOOR REVOLUTION GUARANTEE

Outdoor Revolution products are designed and produced to the very highest of manufacturing standards, using the best quality fabrics or components available for each specific model. Rigorous quality control of finished products is in place.

All manufactured products are:

- Quality controlled to be free from minor defects.
- Fit for the purpose that they are intended for.
- Manufactured to a satisfactory quality.

It is important that correct care is taken when opening, erecting, using, and just as importantly, packing away the product. Following these rules will keep your product in reliable working condition for many years. Failure to adhere to these simple guidelines may cause unnecessary damage to the product (see formal instructions for handling/erection tips). A repair kit is included with each of our products to help resolve any minor issues.

THE WARRANTY

The Outdoor Revolution Warranty lasts for twelve months from the original date of purchase; please keep all receipts or copies of any relevant transaction to substantiate the purchase date. This warranty only covers the workmanship, fabric and components. Any faults found within six months of purchase will be investigated by Outdoor Revolution. Faults found outside of the initial six months of purchase will need to be proven by you, the purchaser, in line with current consumer legislation, after the short term right to reject has concluded. **Please note that this warranty requires registration on our website.**

Retailer will not refund a purchase if no fault is found.

The manufacturer's warranty does not cover the following:-

- General wear and tear over extended periods of use or, seasonal pitching of the product.
- Accelerated UV damage caused by excessive, long term sun exposure.
- Accidental damage caused by but not exclusive to, human, animal or weather.

PLEASE READ THE INSTRUCTIONS CAREFULLY

TIP: Refer to these photographs to assist when pitching your 'Porchlite 260 Air L'.

1. Spread the canvas out on the ground, alongside your motorhome, with the cowl side parallel to your vehicle.



2. Slide the awning piping through the motorhome awning channel, until the awning is in the desired position on the vehicle; we suggest that someone else holds the flysheet up whilst you do this.



3. Peg down the rear pads of the awning against the motorhome, using the adjustable pegging points. Use the strap along the floor, on the inside, to ensure the sides are in the correct position when doing this.



4. Locate the first Boston Valve and securely insert the pump into the valve.

5. Begin to carefully inflate the caravan awning, taking care that the fabric is not caught anywhere, before inflating the Oxygen Air Frame until you can give it a good squeeze; the frame must have space inside for the air to expand, should there be any increases in the ambient temperature.



6. Replace the cap on the 'Boston Valve' and cover the valve with the Velcro flap to prevent water getting inside.

7. Tension the front of the awning as much as you desire, through securing any adjustable pegging straps, whilst using the strap along the floor, on the inside, to ensure the tubes are situated correctly. Please ensure that you do not overtension the fabric whilst doing this.



8. Peg down any remaining pegging points, starting from the corner against the vehicle, before working your way around the caravan awning.

9. Assemble each section of the steel roof tensioning pole; place one end of the pole in the internal front central pocket. Attach the bracket pad (from the repair kit) on your motorhome side, before inserting the opposing end into this.



TROUBLE SHOOTING

<u>PROBLEM</u>	<u>REASON</u>	<u>SOLUTION</u>
The Oxygen Air Frame is deflating after removing the pump.	The 'Boston Valve' has not been properly opened.	Open the Boston Valve and push any air out of the tubes before packing away.
The awning is leaking water.	The canvas requires 'weathering' two to three times before the seams fully seal themselves, therefore you may experience some weeping. This could also be condensation; an inevitable occurrence.	Allow the motorhome awning to get soaked, then fully dried, two to three times. Open any ventilation points to optimise air circulation and reduce condensation.
Bowing and twisting of the tubes.	The tubes may twist inside the sleeves, particularly when packing away, so next time the tube bows...	Unzip the sleeve whilst the tube is deflated and reposition the tube.

IN THE EVENT OF A PUNCTURE

If you have a small puncture in your Oxygen Air Frame Tube, you can easily repair it using the standard puncture repair kit.

- ◆ To remove the Oxygen Air Frame Tube, deflate the tube, then unzip the two protective sleeves over the tube and simply pull it out; please do not unzip the sleeves whilst the tube is inflated.
- ◆ Locate and repair the puncture on the Oxygen Air Frame bladder.
- ◆ Place the Oxygen Air Frame Tube back into the sleeves, in the correct place, with the valves in their respective sockets; make sure that the tube is not twisted.
- ◆ Zip each of the two sleeves back up fully.
- ◆ Inflate the Oxygen Air Frame Tube, ensuring that the puncture has been repaired.
- ◆ If this process doesn't work, you may need to purchase a new bladder.

****Spare air-frame bladders can be purchased to replace damaged ones. Visit the [spares](http://www.outdoor-revolution.com) section at: www.outdoor-revolution.com or contact us on 01924 455 313.**

****Awnings & Tents will not be replaced because of damaged bladders****

PACKING AWAY YOUR MOTORHOME AWNING

- ◆ Zip up any windows and doors before deflating.
- ◆ Unpeg all guylines, storm straps and most of the pegs around the motorhome awning, leaving only each of the four corners pegged out.
- ◆ Open the Boston Valve.
- ◆ Unpeg each of the four corners.



Allow the motorhome awning to collapse on itself, compressing as much air out of the canvas as possible.

Fold the motorhome awning on itself vertically to form a rectangular shape.



Fold the motorhome awning on itself to create a streamlined shape. Measure the width of the motorhome awning against the bag to ensure that it will fit inside. Begin rolling the awning, compressing air out as you roll.

Rotate the rolled motorhome awning onto the bag and pull the sides up around it, before zipping up the bag.



10. We suggest purchasing some 'Endurance Storm Straps' for further stability during adverse weather conditions. In extreme conditions; we recommend packing away your motorhome awning altogether.

11. Thread the draught skirt through the lower awning channel and peg it down at each side.



12. These triangular flaps can either be pegged in to the inside, in order to overlap the draught skirt, or on the outside; dependent on your personal preference!

WARNING: Never unzip the zips on the protective sleeves whilst the Oxygen Air Frame Tubes are inflated. This will result in the tube bursting/ballooning out of the sleeve, causing damage to the tube and sleeve; this is NOT covered under the warranty!